## **Seat Belt for Forklifts**

Forklift Seat Belts - Explained in the Regulation guidelines are the application of seatbelts and operator restraints on lift trucks. It says that the accountability falls on the employers' to be able to ensure that every machine, piece of equipment and tool is used correctly utilized in accordance to the instructions of the producer.

Rough Terrain lift trucks ought to meet the regulations of ANSI Standard ASME B56.6-1992 in regards to their use, design, maintenance, inspection and fabrication.

Side boom tractors and mobile machine together with a Rollover Protective Structure, or ROPS for short, need to have seat belts which satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile equipment has seat belts required by law, the operator and subsequent passengers should make sure they use the belts whenever the vehicle is in motion or engaged in operation in view of the fact that this can cause the equipment to become unsteady and thus, not safe.

If a seat belt or other operator restraint is required on a forklift.

While working a forklift, the seat belt requirements will depend on a number of factors. Contributing factors to this determination may include whether or not the the lift truck is outfitted along with a Rollover Protective Structure, the type of lift truck itself and the year the lift truck was actually manufactured. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to an operator restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is intended to be able to help the driver in lessening the danger of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device may comprise a seat belt, although a seat belt is not necessarily a part of such machine or system.